



*Antenna Factory, Inc.*

[www.antennafactory.com](http://www.antennafactory.com)  
Toll Free: 877-288-9112 Fax: 847-584-9952

**BP870-16.1-120**

## Specifications:

<b>Frequency Range</b>	870-960 MHz
<b>Gain</b>	16.1 dBi
<b>3D Beamwidth Vertical Plane</b>	7°
<b>3D Beamwidth Horizontal Plane</b>	120°
<b>F/B Ratio</b>	≥ 27dB
<b>VSWR</b>	≤ 1.35
<b>Nominal Impedance</b>	50 ohm
<b>Polarization</b>	Vertical
<b>Maximum Input Power</b>	500 W
<b>Lightning Protection</b>	All metal parts grounded
<b>Intermodulation</b>	≤ 110
<b>Connector</b>	N Female or 7/16 DIN Female
<b>Dimension</b>	2438mm × 305mm × 127mm / 7.20 ft × 1.0 ft × 0.42 ft
<b>Weight</b>	9 kg / 19.84 lb
<b>Rated Wind Velocity</b>	216 km/h / 135 mph
<b>Radiating Elements Material</b>	Brass
<b>Back Panel Material</b>	Aluminum Alloy Passive Plane
<b>Radome Material</b>	Fiberglass

Every effort is made to insure the product specifications are complete and accurate.  
However, omissions, changes to product specifications and design changes may occur without notice.